



PHOTO
(P01WS Variant)

DESCRIPTION

Grade 3, Class II 8 terminal keyswitch.
DPCO operation.

VARIANTS

P01	P01W	P01S	P01WS
Silver Keys differ	White Keys differ	Silver Keys differ Security screws	White Keys differ Security screws
P02	P02W	P02S	P02WS
Silver Keys alike	White Keys alike	Silver Keys alike Security screws	White Keys alike Security screws

S variants supplied with matching tool for fixings
All variants supplied with 2x keys
Key blanks available, part code POKEY

ACTIVATION

Key switch - latches in position, key removable in both positions.
Microswitch tamper - operates on lid removal.

WIRING

6x terminals for DPCO (COM, N/O, N/C).
2x terminals for tamper loop.

MATERIALS

Die cast aluminium casing.

TEMPERATURE RANGE

-40 to +50 degrees Celsius.

ELECTRICALLY RATED AS FOLLOWS

0—100v DC, max 500mA
0—250v AC, max 2A



KNIGHT
FIRE & SECURITY

Unit 84 Seawall Road Ind. Estate
Cardiff UK CF24 5TH
Tel: +44 (0) 2920 488 129
Fax: +44(0) 2920 489 132

Drawing #: P01, P02
Drawn: Gareth Carpenter
Date: 01/07/2024
Revision: 1

All dimensions in mm
Do not scale



© Knight Fire & Security Products Ltd
All cases of infringement will be pursued.